

LED Globe

GL-19AA

> Introduction

The GL-19AA will eventually become the chief substitutes for incandescent lamps. With the compact and beautiful appearance, the globe has great heat-sinking properties. It is also mothproof rated. In addition, it can be substituted for those lamps with E27 fixtures. This globe has great energy saving capacity. The simple installation can minimize the maintenance costs.

> Application Environment



The LED globe can provide soft and symmetrical lighting without strobe. It can be used in places, such as residential homes, markets, hotels/motels, or offices.

> Technical Parameters

Part NO.	Size (mm)	Weight (g)	Color
GL-19AA	100×Φ59	55	White

Parameter	Min.	Standard	Max.	Remark
Operating Voltage (V AC)	100	110/220	250	/
Operating Frequency (Hz)	/	50/60	/	/
Power (W)	/	2.0	/	/
CCT (K)	5,500	6,000	6,500	Day Light
	3,500	4,000	4,500	Cool White
	2,500	3,000	3,500	Warm White
Luminous Flux (lm)	/	100	/	Day Light
	/	100	/	Cool White
	/	90	/	Warm White
Operating Temperature (°C)	5	25	40	/
Operating Humidity	10%	60%	90%	/
Storage Temperature (°C)	-40	25	80	/
Body Material	PC+Glass			
Packaging	20PCS /Carton (K5K5K)			
Package Size (mm)	622×420×155 (20PCS)			
Design Life (Hr)	15,000			



CAP: E27
Design Picture

