

LED Ceiling Light

CL-20C

> Introduction

The CL-20C will eventually become the chief substitutes for fluorescent lights. It adopts punching structure. With the compact and beautiful appearance, the ceiling light has great heat-sinking properties. It is also mothproof rated. The CL-20C integrates a LED light source and power driver. The product's long lifetime and excellent lumen maintenance minimize the hassle of relamping while reducing maintenance costs. In the product, high-tech light guide plate (LGP) is used to provide shadowless lighting. There is no mercury in the product, so it is a green image.

> Application Environment



The CL-20C can provide soft and symmetrical lighting without strobe. It can be used in places, such as hotels/motels, offices, auditoria, markets, carparks or schools.

> Technical Parameters

Part NO.	Size (mm)	Weight(kg)	Color	
CL-20C	1,260×203×43	5.2	White	
Parameter	Min.	Standard	Max.	Remark
Operating Voltage(V AC)	100	110/220	240	/
Operating Frequency(Hz)	/	50/60	/	/
Power(W)	50	55	60	/
CCT(K)	/	6,500	/	Day Light
	/	5,700	/	
	/	3,000	/	Warm White
	/	2,700	/	
Luminous Flux(lm)	3,000	3,300	/	Day Light
	2,300	2,700	/	Warm White
Color Rendering Index	/	70	/	/
Operating Temperature(°C)	5	25	40	/
Operating Humidity	10%	60%	90%	/
Storage Temperature(°C)	-40	25	80	/
Quantity of LED(PCS)	640			
Body Material	Steel + PC			
Packaging	1PCS/Carton(K5K5K)			
Package Size(mm)	1,285×230×80			
Design Life(Hr)	40,000			



Design Picture

