

LED Light

CL-48AA

> Introduction

The LED light adopts punching structure. With the compact and beautiful appearance, the ceiling light has great heat-sinking properties. It is also mothproof rated. The LED light integrates a LED light source and power driver. The product's long lifetime and excellent lumen maintenance minimize the hassle of relamping while reducing maintenance costs. In the product, high-tech light guide plate (LGP) is used to provide shadowless lighting. There is no mercury in the product, so it is a green image.

> Application Environment



Picture of lights installed in Overseas Chinese Town (OCT)


The light is applied for general lighting and accent lighting. It can be widely used in many places, such as living rooms, offices, exhibition halls, and factories.

Note: The power and size of the downlight can be customized. It is going to swap out traditional lights.



Design Picture

> Technical Parameters

Part NO.	Size(mm)		Weight(g)	Color
CL-48AA	45xΦ195		800	White
Parameter	Min.	Standard	Max.	Remark
Operating Voltage(V AC)	100	110/220	240	/
Operating Frequency(Hz)	/	50/60	/	/
Power(W)	/	12	/	/
CCT(K)	/	6,530	/	Day Light
	/	5,665	/	Warm White
	/	3,045	/	
	/	2,725	/	
Luminous Flux (lm)	/	740	/	Day Light
	/	650	/	Warm White
Size of installation hole (mm)				
Operating Temperature(°C)	5	25	40	/
Operating Humidity	10%	60%	90%	/
Storage Temperature(°C)	-40	25	80	/
Body Material	AL			
Packaging	10PCS/Cartron(K5K5K)			
Package Size (mm)	490×385×295(10PCS)			
Design Life(Hr)	40,000			

