

LED Spot Light

DL-16AB

> Introduction


For general lighting and accent lighting, the DL-16AB will eventually become the chief substitutes for traditional lamps. It adopts heat-conductive plastic. With the compact and beautiful appearance, the spot light has great heat-sinking properties. It is also mothproof rated. In addition, it can be substituted for those lamps with GU5.3 fixtures. When the spot light is operating, the soft lighting diffuses symmetrically, showing a professional optical design. The DL-16AB is specially used to illuminate foods, organic materials or painting.

> Application Environment



The DL-16AB can provide bright and symmetrical lighting without strobe. It can be used in places, such as markets, hotels/motels, or exhibition places.

> Technical Parameters

Part NO.	Size(mm)		Weight(g)	Color
DL-16AB	52×Φ50		56	Gray+Black
Parameter	Min.	Standard	Max.	Remark
Operating Voltage(V AC/DC)	/	12	/	/
AC Operating Frequency(Hz)	/	50/60	/	/
Power(W)	/	5.0	/	/
CCT (K)	/	6,530	/	Day Light
	/	5,665	/	
	/	3,045	/	Warm White
Luminous Flux (lm)	/	300	/	Day Light
	/	280	/	Warm White
Operating Temperature(°C)	5	25	40	/
Operating Humidity	10%	60%	90%	/
Storage Temperature(°C)	-40	25	80	/
Installation fixture				<p>Note: The distance between the lighting surface and pin holder is more than 47mm.</p>
Emitting Angle				25°
Body Material				AL+ ABS
Packaging				50PCS /Carton(K5K5K)
Package Size (mm)				615×225×385 (50PCS)
Design Life(Hr)				25,000



CAP:GU5.3
Design Picture

Please refer to the product itself for the actual appearance

