

LED Spot Light

DL-16GU

> Introduction

For general lighting and accent lighting, the DL-16GU will eventually become the chief substitutes for traditional lamps. It adopts heat-conductive plastic. With the compact and beautiful appearance, the spot light has great heat-sinking properties. It is also mothproof rated. In addition, it can be substituted for those lamps with GU10 fixtures. When the spot light is operating, the soft lighting diffuses symmetrically, showing a professional optical design. The DL-16GU is specially used to illuminate foods, organic materials or painting.

> Application Environment



The DL-16GU can provide bright and symmetrical lighting without strobe. It can be used in places, such as markets, hotels/motels, or exhibition places.

> Technical Parameters

| Part NO. | Size (mm) | Weight(g) | Color |
|----------|-----------|-----------|------------|
| DL-16GU | 68×Φ50 | 76 | Gray+Black |

| Parameter | Min. | Standard | Max. | Remark |
|----------------------------|----------------------|----------|------|------------|
| Operating Voltage(V AC/DC) | 100 | 110/220 | 250 | / |
| AC Operating Frequency(Hz) | / | 50/60 | / | / |
| Power(W) | / | 4.7 | / | / |
| CCT (K) | / | 6,500 | / | Day Light |
| | / | 5,700 | / | Warm White |
| | / | 3,000 | / | |
| Luminous Flux (lm) | / | 320 | / | Day Light |
| | / | 300 | / | Warm White |
| Operating Temperature(°C) | 5 | 25 | 40 | / |
| Operating Humidity | 10% | 60% | 90% | / |
| Storage Temperature(°C) | -40 | 25 | 80 | / |
| Emitting Angle | 30° | | | |
| Body Material | AL+ PC | | | |
| Packaging | 50PCS /Carton(K5K5K) | | | |
| Package Size (mm) | 610×260×385 (50PCS) | | | |
| Design Life(Hr) | 25,000 | | | |



CAP:GU10
Design Picture

